



**FLOOR AREA:** 10,430 SQM  
**LOADING:**  
**FLOOR:** 7.5 kpa  
THE SLAB CAN CARRY A SINGLE AXLE LOAD OF SIX (6) TONNES IN LIMITED REPETITION  
**ROOF:** POINT LOAD OF 250kg. CAN BE APPLIED DIRECTLY TO THE I BEAMS IF REQUIRED.  
**SUPPLY CAPACITY:**N1.1, N1.2, N1.3 = 3 x 400A  
NOTE: BUILDING SPECIFICATIONS FOR B-01 (FORMALLY N-1) AS SUPPLIED BY DARYL JACKSON ARCHITECTS 14-07-2006

**SERVICES**

DB OR COMMS. RACK	OUTLET 240 10 AMP TYP.	OUTLET 3 PHASE	FIRE HOSE REEL	EXTINGUISHER	COLD WATER POINT	SEWER OUTLET
VENUE EXIT	DEFIBRILLATOR	EXHAUST FAN	AIR CONDITIONER	GAS ISOLATION VALVE	FIRE HYDRANT	

**AREAS TO BE KEPT CLEAR**

NO BUILD ZONE



Disclaimer  
This drawing is a representation only. Royal Melbourne make no representations about the accuracy of the information contained herein, not for construction or event build purposes. All measurements & equipment need to be checked on site. Do not scale. If in doubt, consult the Duty engineer or Operations Manager.  
Copyright  
All rights reserved. This work is copyright & cannot be reproduced or copied in any form or by any means (graphic, electronic or mechanical, including photocopying) without the written permission of the content provider. Any licence, expressed or implied, to use this document for any purpose whatsoever is restricted to the terms of the agreement or implied agreement between the content provider and the instructing party.

**BUILDING 01**  
**EXHIBITION PAVILION**

Venue Site plan with services no build zone & Grid reference

May 23 V-01

Venue

Detail

Issue