



FLOOR AREA: GROND LEVEL ONLY 2,096 SQM
LOADING:
FLOOR: 7.6 kpa
 MAXIMUM GROSS VEHICLE WIEGHT ALLOWED ON SLAB IS FOUR (4.0) TONNES W/ MAX.30 REPS/DAY
ROOF: THE STRUCTURE CAN CARRY A DEAD LOAD OF 100KG AND MUST BE TIED BACK TO THREE (3) POINTS OF CONTACT
SUPPLY CAPACITY:MDB-H2-500A
 BUILDING SPECIFICATIONS FOR B-08 (FORMALLY H-2) AS SUPPLIED BY DARYL JACKSON ARCHITECTS 14-07-2006

SERVICES

DB OR COMMS. RACK		VENUE EXIT	
OUTLET 240 10 AMP TYP.		DEFIBRILLATOR	
OUTLET 3 PHASE		AIR CONDITIONER	
FIRE HOSE REEL			
EXTINGUISHER			
COLD WATER POINT			
SEWER OUTLET			

AREAS TO BE KEPT CLEAR

NO BUILD ZONE

Disclaimer
 This drawing is a representation only. Royal Melbourne make no representations about the accuracy of the information contained herein, not for construction or event build purposes. All measurements & equipment need to be checked on site. Do not scale. If in doubt, consult the Duty engineer or Operations Manager.
 Copyright
 All rights reserved. This work is copyright & cannot be reproduced or copied in any form or by any means (graphic, electronic or mechanical, including photocopying) without the written permission of the content provider. Any licence, expressed or implied, to use this document for any purpose whatsoever is restricted to the terms of the agreement or implied agreement between the content provider and the instructing party.



BUILDING 08
TOWN SQUARE PAVILION LV-1
 Venue Site plan with services no build zone & Grid reference
 June 23 V-01

Venue
 Detail
 Issue